

Mountain Grout®

Epoxy System

Technical Data:

MG15

ANCHORING

Description: MG15 is a 100% solids, two component, fast setting anchoring epoxy. MG15 is moisture insensitive and will bond to wet or dry concrete, even underwater. MG15 is commonly used to anchor reinforcing bars, smooth dowels, threaded rod and ties into concrete. The thixotropic paste may be used with screen tubes to anchor rods in unreinforced masonry or brick. MG15 can be used vertically or horizontally.

Features:

- Meets ASTM C-881, Type I, II, IV & V, Grade 3, Class A, B & C
- Rapid cure; less than 1 hour
- Bonds to wet or dry concrete; even underwater
- Easily mixed
- Applied horizontally or vertically
- Moisture Insensitive

TEST TYPE	RESULTS	TEST METHOD
Compressive Strength	14,000 psi (min)	ASTM D-695
Tensile Strength	7,250 psi (min)	ASTM D-638
Tensile Elongation	1% minimum	ASTM D-638
Pot Life @75°F	10 Minutes	
Cure Time @75°F	1 hour	
Shore D Hardness	87-82	
Ratio	1:1 by volume	
Color (mixed)	Grey	
Packaging	2 Gallon, 10 Gallon, 22 oz., 11 oz., Cartridges	

MSDS should be read before using Mountain Grout products.

Green Mountain International, Inc.

Ph: 800-942-5151 Fax: 888-632-5360 Int'l: 828-456-9970 Fax: 828-456-9699

URL: <http://www.mountaingrout.com> E-mail: tech@mountaingrout.com