

**Section I – Product and Company Identification****Trade Name:** Mountain Grout**Product Name:** MG06B**Distributed by:**  
Green Mountain International, Inc.  
235 Pigeon Street  
Waynesville, NC 28786  
800-942-5151 US/Canada \* 828-456-9970 International**24 Hr. Emergency Telephone Number:**  
Chemtrec: 800-424-9300**Section II – Hazardous Ingredients**

	CAS#	Current TLV/TWA
Aliphatic Amine Solution	T/S	NE

*Ingredients not precisely identified are not hazardous*

T/S = Trade Secret

NE = Not Established

**Section III – Hazardous Summary****Potential Health Effects: DANGER CORROSIVE – May cause skin and eye burns.****Inhalation:** May cause irritation to upper respiratory tract. Avoid prolonged or repeated inhalation.**Eye Contact:** May cause eye irritation on prolonged or repeated exposure.**Skin Contact:** May cause skin irritation on prolonged or repeated exposure.**Ingestion:** Do not take internally. May cause burns of mouth and throat.**Chronic Effects of Overexposure:** Possible allergic skin reaction.**Section IV – Emergency & First Aid Procedures****Eyes:** Flush with plenty of water and get medical attention. Keep eyelids apart. Wash within 1 minute of contact for maximum results.**Skin:** Promptly wipe clean with paper or cloths and wash with soap and water. Remove contaminated clothing before reuse. Attention should be paid to hair, nose and eyes.**Inhalation:** In case of exposure to high concentration of vapor or mist, remove person to fresh air.**Ingestion:** If large amounts are swallowed, induce vomiting. Seek medical attention. May cause burns to mouth and throat.**Primary Route of Entry:** Inhalation, ingestion, skin and eye contact.**Carcinogenicity:** This product does not contain 0.1% or more of any substance that is listed as a carcinogen by NTP, IARC or OSHA.**Section V – Fire & Explosion Data****Flash Point:** > 171°F (>77°C) **Test Method:** Setaflash Closed Cup**Extinguishing Media:** Water, foam, carbon dioxide, dry chemicals or fog.**Unusual Fire and Explosion Hazards:** May produce hazardous fumes or hazardous decomposition products.**Special Fire Fighting Procedures:** Firefighters should wear protective goggles and self-contained breathing apparatus to avoid inhalation of smoke or vapors. Remove all ignition sources.**Section VI– Spill or Leak Procedures****Steps to be taken in case material is released or spilled:** Ventilate area. Absorb spill with suitable absorbent material and place into a closed container. Prevent material from entering waterways. Wear protective equipment during cleanup. Use eye and skin protection.**Waste Disposal Method:** Incinerate or use biological treatment in accordance with federal, state and local regulations. For further information, contact: EPA - RCRA HOTLINE (1-800-424-9346).

## **Section VII – Storage and Handling**

**Storage Temperature (min/max):** 65° and 85° F (18° and 29° C)

**Average Shelf Life:** 2 years from date of manufacturing in unopened containers.

**Precautions in Handling & Storage:** This material may cause sensitization. Do not get in eyes, on skin or clothing. Do not allow clothing to contact skin. Avoid contact with vapors or fumes.

**Special Precautions:** Avoid contact with skin and eyes. Avoid breathing vapor. Keep container closed when not in use. Avoid prolonged exposure to light. Store at temperatures below 120°F. Remove all contaminated clothing, shoes, belts, and other leather goods immediately. Solvents should not be used to clean skin because of increased penetration potential. Wash contaminated clothing before reuse.

## **Section VIII – Employee Protection Recommendations/Exposure Control**

**Respiratory Protection:** Should be worn to avoid breathing spray mist, heated vapors or if TLV is exceeded. Acid vapor type.

**Ventilation:** Local exhaust and general ventilation recommended.

**Skin:** Wear impervious gloves. Apply barrier cream before exposure. Do not apply cream after exposure.

**Eyes:** Chemical splash goggles.

**Other Protective Equipment:** As required to prevent wetting of skin and clothing.

## **Section IX – Physical Data**

The following data represents approximate or typical values. They do not constitute product specifications.

<b>Appearance:</b>	Paste
<b>Color:</b>	Gray
<b>Odor:</b>	Amine
<b>Boiling Point:</b>	N/A
<b>Viscosity @ 75°F:</b>	300 cps (mixed)
<b>Density:</b>	1.07
<b>Percent Volatile:</b>	0% by weight
<b>Water Miscibility:</b>	Slight

## **Section X – Stability and Reactivity Data**

**Stability:** Stable. **Hazardous Polymerization:** Will not occur.

**Incompatibility (Materials to avoid):** Strong oxidizer, epoxy resin, and amine mixtures especially when hot.

**Hazardous Decomposition Products:** None known.

**Conditions to Avoid:** Heat and warm storage.

## **Section XI – Toxicological Information**

**Carcinogenicity:** This product does not contain 0.1% or more of any substance that is listed as a carcinogen by NTP, IARC or OSHA.

## **Section XII – Supplemental Information**

**Regulatory Information:** Corrosive Liquid

**SARA Hazard Classification:** SARA Title III Regulations (40 CFR 370): N/A

**SARA Section 313 Listed Ingredients:** This material does not contain any substance that is subject to the reporting requirements of 40 CFR 372.

**DOT Proper Shipping Name:** Corrosive Liquid N.O.S.

**UN Number:** UN 1760

**HMIS Ratings:** Health - 3 Flammability - 2 Reactivity - 1 Other - Corrosive

**Disclaimer:** The information in this MSDS was obtained from sources that we believe are reliable. The information is provided without warranty, implied or expressed, concerning accuracy. Green Mountain International, Inc. assumes no legal responsibility for use or reliance on this information. This MSDS is provided solely for the purpose of conveying health, safety, and environmental information. This MSDS is not a specification data sheet. Some of the information and conclusions are derived from sources other than test data on the material itself.

Distributed by:  
Green Mountain International, Inc.  
235 Pigeon Street, Waynesville, NC 28786  
Ph: 800-942-5151 Fax: 888-632-5360  
Int'l: 828-456-9970 Fax: 828-456-9699  
[www.mountaingrout.com](http://www.mountaingrout.com)