

Mountain Grout®

Hydrophobic Polyurethane System

CARTRIDGE SYSTEMS

Description: Mountain Grout P.L.U.G.S. cartridge system is a two-component polyurethane resin designed to fill voids or stop water leaks. The formula reacts in 30 to 45 seconds and will not generate extreme exothermic temperatures. For application procedures and MSDS see P.L.U.G.S. at www.mountaingrout.com

TEST TYPE	RESULTS	TEST METHOD
Density	3 lbs.	ASTM D-1622
Water Absorption (Volume Confined)	<1%	ASTM D-2127
Shear Strength	50 PSI	ASTM C-273
Tensile Strength	75 PSI	ASTM D-1623
Elongation	5%	ASTM D-1623
Viscosity	250 CPS "A" Side	500 CPS "B" Side
Color	Amber	
Shrinkage	<1%	
USDA Approved	YES	
USDOT Shipping Data	UNREGULATED CLASS 55	

*MSDS should be read before using Mountain Grout products.

Cox dispensing tools are available from your distributor or Green Mountain International as are extra supply items, static mixers and nuts.

Mountain Grout is a registered trademark of...

Green Mountain International, Inc.

Ph: 800 942 5151 Fx: 888 632 5360 Int'l: 828 456 9970 Fx: 828 456 9699

URL: <http://www.mountaingrout.com> E-mail: tech@mountaingrout.com